

JBA[®] performance exhaust

Corporate Office: PerTronix Inc. 440 E. Arrow Highway, San Dimas, California 91773 * Phone 909.599.5955 • FAX 909.599.6424

Installation Instructions and Warranty Information

1683S 2015-16 Ford F-150 5.0 V8



This Product has been granted a California Air Resources Board (CARB) "E.O" (Executive Order) Exemption, or is considered a Direct Replacement or Consolidated Replacement part. It is 50 State Legal when installed on the appropriate vehicle per the Manufacturer Application guide and Installation Instructions.

Read all instructions carefully before attempting installation.

WARNING

This product can expose you to chemicals which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product

PerTronix® thanks you for choosing JBA HEADERS, the best fitting, highest quality header on the market. In order to realize the full potential of our good fit, please read and understand these instructions completely prior to starting work.

Check to make sure you received the proper parts for your application. The header number will be stamped on the engine flange. If you are unsure you have received the proper parts call before you start work.

Be sure to work safe! Whenever you work under the vehicle be sure that it is located on level, solid ground and is supported by adequate safety stands! Remember: Hot asphalt will not support most jack stands!

Many factors affect the installation of headers, some of which are broken or aftermarket motor mounts, accidents that impact the configuration of the frame, and/or the installation of different engines or aftermarket cylinder heads.

Attention Customers breaking in new engines: Due to the extreme heat generated during the break-in process, the appearance of the ceramic coating may be altered in certain areas. The protection characteristics and thermal barrier properties of the coating is never compromised. It is recommended that a cast iron manifold or old set of headers be used for this process.

Notice: The coating of these headers can be marred or scratched during installation. If the header needs to be returned and is damaged, you will be charged for recoat.

JBA uses sealing beads on all its headers. We have found that when installed correctly, the raised bead around each port increases the pressure exerted on the gasket directly adjacent to the port and effectively prevents leaking gaskets. It is normal for the flange to be raised off the cylinder head the thickness of the sealing bead. It is important when installing the header, to install all bolts loosely, then tighten evenly to ensure the flat installation of the flange. The torque sequence from one flange to another will vary, but generally every bolt on a header should be first fit snug, starting from the inside of the flange working out, alternating from top to bottom so that the bolt connects the flange to the manifold to the point where they barely touch. Second, using the same inside-out pattern, tighten each bolt until finished. This method will help prevent leakage and will give the user the best possible performance out of their pair of headers.

1. Place vehicle in a location where the floor is solid and flat, with adequate lighting. Do not attempt to work on a hot engine. Heat causes metal to expand and makes removal of fasteners difficult at best. Disconnect the negative battery cable from the battery. Raise the front of the vehicle to obtain adequate access to the bottom exhaust manifold flanges. Use large-base jack stands to support the vehicle. Do not rely on the jack! Block the tires to prevent the vehicle from rolling off the jack stands.
2. Apply penetrating oil on all accessible fasteners and fittings before attempting to remove them.
3. From underneath the vehicle, unbolt factory the exhaust system from the exhaust manifold collectors. Pry the exhaust system back about 1/2" to gain workspace. Spraying the rubber exhaust hangers with WD-40 may help.
4. Remove the passenger side front tire, and inner fender panel. The inner fender panel is held in place with a combination of hex head screws, and "Christmas Tree" fasteners which "snap" off.

Passenger Side Header

5. Place a jack, with a board between the jack and the oil pan, underneath the motor. Remove the 2 21mm motor mount nuts and raise the engine approximately 1".
6. Remove the nuts and studs attaching the manifold to the head. Remove the manifold.
7. Remove the gasket and any gasket material or any carbon deposits that remain on the head surface. The use of a gasket removal agent or scraper will ease the removal of any gasket material. Use care not to get debris into ports.
8. Remove all the factory exhaust studs.
9. Slip the header into place through the fenderwell.
10. Apply anti seize to the header bolts. Slip the gasket in place, Install the supplied Header bolts and star washers. Tighten fasteners in an alternating sequence. Torque to 14-18 lbs. ft.
11. Lower the motor and tighten the motor mount bolts.
12. Install the inner fender panel and front wheel.

Driver's Side Header

1. From under the hood, remove the top two forward exhaust manifold nuts.
2. Place a jack, with a board between the jack and the oil pan, underneath the motor. Remove the 24mm motor mount bolt (This bolt will be VERY tight) and jack the motor up approximately 1". Remove the 3 13mm motor mount plate bolts from the block and remove the plate.
3. Remove the remaining 6 nuts attaching the manifold to the head. Remove the manifold and then remove all eight studs.
4. Remove the gasket and any gasket material or any carbon deposits that remain on the head surface. The use of a gasket removal agent or scraper will ease the removal of any gasket material. Use care not to get debris into ports.
5. Slip the header into place from underneath the truck. Apply anti seize to the header bolts. Slip the gasket in place, Install the supplied Header bolts and star washers. Tighten fasteners in an alternating sequence. Torque to 14-18 lbs. ft.
6. Reinstall the motor mount plate to the block and tighten the 3 13mm bolts. Lower the motor and re install the 24mm motor mount bolt
7. Apply a small amount of O2 sensor safe RTV silicone around the flares on the factory exhaust system then reconnect the factory catalytic convertors and exhaust system to the new headers using the supplied 3/8-16X 2-1/2" collector bolts, nuts, and lock washers.
8. Check to make sure that all the wiring, fuel lines, transmission cooler lines, brake lines, hoses, etc. are clear of the headers or any exhaust components and reroute or relocate those components as necessary.
9. Reconnect the battery.
10. Start the engine, check for leaks and test drive. Let the engine cool and then re-torque the header bolts.
11. Periodically check and retighten the header bolts.

Parts List:

- (1) Driver's Side Header Assembly
- (2) Header flange gaskets
- (16) 10mm Lock washers
- (4) 3/8-16 Nuts
- (1) CARB EO Sticker D-57-33

- (1) Passenger's Side Header Assembly
- (16) 10-1.25mm Header bolts
- (4) 3/8-16 x 2.5" Collector Bolts
- (4) 3/8" Lockwashers



440 E. Arrow Hwy.
San Dimas, CA 91773
(909) 599-5955

This vehicle is equipped with:

**JBA Headers # 14XXS, 16XXS
18XXS, 20XXS**

Legal for sale and installation in California

CARB EXECUTIVE ORDER D-57-33

WARNING

This label is required to aid in passing the California smog check program. This label must be installed in an underhood location that is readily visible.

LIMITED ONE YEAR WARRANTY

All JBA HEADERS and exhaust products are guaranteed, to the original purchaser, to be free of defects in materials and workmanship for one year. This warranty covers the replacement or repair of the product only and does not cover the cost of removal and installation, customer applied aftermarket coatings or any discoloration or corrosion of finished surfaces.

Damage or product failure resulting from collision, improper installation, off-road use, road hazards, the use of exhaust insulating wrap or like products or rust occurring after installation, is not covered by the warranty. The warranty extends only to the original purchaser.

Should a part become defective it should be returned to the original selling retailer and must be accompanied with the sales receipt. If there is no retailer in your area, call the factory for a return authorization and return your part prepaid to the factory for inspection. PerTronix reserves the rights to replace or repair the alleged defective part and return the part freight collect.

JBA
performance**exhaust**®

